



XANTUS PRODUCTS

Injectable UV Dye

- Much easier to use than other dyes
- Very affordable
- No need to pump down units
- Can be installed in seconds
- Contains no methanol



Treats
Up to 5 tons

Description:

Our exclusive UV Dye Direct Inject simplifies tracking down leaks. No more mess, no more measuring, and no more refilling! Simply inject Firefly UV Dye and it will accumulate around all leak areas, and use UV light and glasses to locate the leaks! To repair most leaks use our Max Seal to permanently seal the leak.

Application:

- Designed for split systems, heat pumps, microchannel coils, packaged units, and mini splits
- Clear tube so you can see the dye go in
- No injection hose or caulk gun needed
- No need to pump down units
- Ultra concentrated formula
- One time use

Packaging:

Firefly UV Dye Direct Inject

#23-201

Directions for Use:

1. Turn the a/c system on and verify the unit is running. Connect Firefly UV Dye to the low-side service port of the system. (This is generally the large line.)
2. Connect the manifold refrigerant hose to the refrigerant supply tank. Verify the high and low side valves on the manifold are closed before proceeding. Purge the low pressure hose when connecting to Firefly UV Dye.
3. Open low-side valve and watch for the tube to clear. (This will ONLY take a few seconds!) Turn off low-side manifold valve as soon as the tube is clear. Turn off refrigerant gas. Verify the system is charged to Manufacturer's specifications! Disconnect low-side hose from Maximum Dye. Install service port cap. Run the a/c unit at least one hour after installing Firefly UV Dye. **(Do not bend or kink hose!)**

